

Triple or Quad Flange Earplugs

Hearing loss is preventable. Wear your hearing protection.



Place the stem of the **TF** earplug into the seating device or firmly grasp the stem of the **QF** earplug.



The last flange of the **TF** earplug should be flush with the ear canal opening.

The last flange of the **QF** earplug may or may not be flush with the ear canal opening.



Gently push or twist earplug into ear canal.



When inserted correctly tension should be felt when lightly pulling on the stem.

Protect Your Hearing

WEAR

- ▶ When fitted correctly, your own voice will sound deeper, as if talking inside a barrel.
- ▶ Twist rather than pull earplugs out of ear canal
- ▶ Re-insert periodically if worn for long periods

CARE

- ▶ Wash earplugs with warm soapy water
- ▶ Allow earplugs to completely dry before placing into the ear or earplug case
- ▶ Store earplugs in an earplug case to minimize loss

Ordering Quad Flange

- ▶ Uncorded, NSN 6515-01-492-0443
- ▶ Corded, NSN 6515-01-492-0458

Ordering Triple Flange

- ▶ Small (green) NSN 6515-00-442-4821
- ▶ Medium (orange) NSN 6515-00-442-4818
- ▶ Large (blue) NSN 6515-00-467-0092
- ▶ Earplug case with inserter: NSN 6515-01-100-1674

For more information on noise and hearing loss contact the **Army Hearing Program** at: 410-436-3797, DSN: 584-3797
phc.amedd.army.mil/topics/workplacehealth/hrc/pages/default.aspx

